

View Online at <https://aerobasegroup.com/nsn/5962-01-207-6582>

Body Length:

Between 0.355 inches and 0.400 inches

Body Width:

Between 0.245 inches and 0.280 inches

Body Height:

0.180 inches

Maximum Power Dissipation Rating:

680.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

5820-01-145-8305 receiver-transmitter, radio

Features Provided:

High slew rate and low power and monolithic and high impedance and low bias

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

Dual 2 input

Design Function And Quantity:

2 amplifier, operational, general purpose

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit linear- low power, dual biffet or map

Voltage Rating And Type Per Characteristic:

-18.0 volts power source and 18.0 volts power source

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

3 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0