

View Online at <https://aerobasegroup.com/nsn/5962-01-207-6582>

**Body Length:**

Between 0.355 inches and 0.400 inches

**Body Width:**

Between 0.245 inches and 0.280 inches

**Body Height:**

0.180 inches

**Maximum Power Dissipation Rating:**

680.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

5820-01-145-8305 receiver-transmitter, radio

**Features Provided:**

High slew rate and low power and monolithic and high impedance and low bias

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Input Circuit Pattern:**

Dual 2 input

**Design Function And Quantity:**

2 amplifier, operational, general purpose

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit linear- low power, dual biffet or map

**Voltage Rating And Type Per Characteristic:**

-18.0 volts power source and 18.0 volts power source

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

3 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0