NSN 5962-01-207-7967

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-207-7967 **Body Length:** 1.400 inches **Body Width:** 0.805 inches **Body Height:** 0.232 inches **Maximum Power Dissipation Rating:** 3.0 watts **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius Storage Tempurature Range: -55.0 to 135.0 degrees celsius **Features Provided:** Hermetically sealed and low power and w/inhibit **Inclosure Material:** Ceramic or metal **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 6 input **Design Function And Quantity:** 1 transceiver **Terminal Surface Treatment:** Gold Voltage Rating And Type Per Characteristic: 7.0 volts power source and 18.0 volts power source **Time Rating Per Chacteristic:** 300.00 nanoseconds propagation delay time, low to high level output and 300.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surfaces option gold **Precious Material:** Gold **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 24 printed circuit Shelf Life: N/a

Demilitarization: Yes - demil/mli

Unit Of Measure:

NSN 5962-01-207-7967

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0