

View Online at <https://aerobasegroup.com/nsn/5962-01-208-2183>

Body Length:

0.785 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

0.185 inches

Maximum Power Dissipation Rating:

122.0 milliwatts

Operating Temperature Range:

-55.0 to 125.0 degrees celsius

Storage Temperature Range:

-65.0 to 150.0 degrees celsius

Features Provided:

Monolithic and schottky and hermetically sealed

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Quad 2 input

Design Function And Quantity:

4 gate, nand

Case Outline Source And Designator:

D-1 mil-m-38510

Time Rating Per Characteristic:

4.00 nanoseconds propagation delay time, low to high level output and 4.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminal surfaces option gold

Precious Material:

Gold

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0