## NSN 5962-01-208-2361

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-208-2361

| View Online at https://aerobasegroup.com/nsn/5962-01-208-2361  |
|--|
| Body Length:   |
| Between 0.770 inches and 0.810 inches  |
| Body Width:  |
| Between 0.280 inches and 0.300 inches  |
| Body Height:   |
| Between 0.060 inches and 0.120 inches  |
| Maximum Power Dissipation Rating:  |
| 450.0 milliwatts   |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| Features Provided:   |
| Electrostatic sensitive and low power and hermetically sealed  |
| Inclosure Material:  |
| Ceramic  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Output Logic Form:   |
| Complementary-metal oxide-semiconductor logic  |
| Input Circuit Pattern:   |
| 9 input  |
| Design Function And Quantity:  |
| 1 converter, digital to analog   |
| Terminal Surface Treatment:  |
| Gold   |
| Voltage Rating And Type Per Characteristic:  |
| 7.0 volts power source   |
| Precious Material And Location:  |
| Terminal surfaces gold   |
| Precious Material:   |
| Gold   |
| Test Data Document:  |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity:  |
| 16 printed circuit   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

Demilitarization:

Yes - demil/mli

## NSN 5962-01-208-2361

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0