NSN 5962-01-208-3614

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-208-3614

view Offiline at https://aerobasegroup.com/hist//3302-01-200-3014
Body Length:
Between 0.930 inches and 1.010 inches
Body Width:
Between 0.245 inches and 0.300 inches
Body Height:
0.185 inches
Operating Tempurature Range:
-55.0 to 125.0 degrees celsius
Storage Tempurature Range:
-65.0 to 150.0 degrees celsius
Features Provided:
Hermetically sealed and high speed and low power and schottky and cascadable and w/enable
Inclosure Material:
Ceramic or glass or metal
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
17 input
Design Function And Quantity:
1 comparator
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
22.00 nanoseconds propagation delay time, low to high level output and 21.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminal surfaces option gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
20 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

NSN 5962-01-208-3614

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0