NSN 5962-01-208-7309

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-208-7309 **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 900.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and w/resistor and positive outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 1 input and dual 2 channel **Design Function And Quantity:** 2 switch, analog, single pole double throw **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 36.0 volts power source **Time Rating Per Chacteristic:** Err-060 hand pull and err-060 hand **Precious Material And Location:** Terminal surface option gold **Precious Material:** Gold **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5962-01-208-7309

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0