NSN 5962-01-209-2389

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-209-2389

View Online at https://aerobasegroup.com/nsn/5962-01-209-2389
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
0.250 inches
Maximum Power Dissipation Rating:
600.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+125.0 degrees celsius
End Application:
1270-01-142-2855 target designator
Features Provided:
Hybrid and hermetically sealed and low noise
Inclosure Material:
Ceramic or glass or metal
Inclosure Configuration:
Can
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 amplifier, operational, general purpose
Case Outline Source And Designator:
To-5 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
15.0 volts power source
Precious Material And Location:
Terminal surfaces optional gold
Precious Material:
Gold
Test Data Document:
58260-13084255 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
8 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: Yes - demil/mli

NSN 5962-01-209-2389

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0