NSN 5962-01-209-4000

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-209-4000

Overall Length:
0.810 inches
Overall Height:
0.325 inches
Body Length:
0.810 inches
Body Width:
0.295 inches
Body Height:
0.180 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+100.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and w/enable and positive outputs
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Metal oxide-semiconductor logic
Input Circuit Pattern:
11 input
Current Rating Per Characteristic:
50.00 milliamperes output
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 20.0 volts power source
Capitance Rating Per Characteristic:
10.00 picofarads interstage and 7.00 preset picofarads interstage
Time Rating Per Chacteristic:
Err-060 perforated steam pipe
Memory Device Type:
Ram
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:

16 printed circuit

NSN 5962-01-209-4000

Memory Microcircuit - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0