## NSN 5962-01-210-6433

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-210-6433 **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 200.0 milliwatts **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and bipolar and negative outputs and positive outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 2 input **Design Function And Quantity:** 2 amplifier, log **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 8.0 volts power source **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli

Fiig:

A458a0