## NSN 5962-01-211-6320

Digital Microcircuit - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5962-01-211-6320

## **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 200.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+175.0 degrees celsius **Features Provided:** Monolithic and burn in and hermetically sealed and w/reset **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 6 input **Design Function And Quantity:** 1 latch, addressable **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 18.5 volts power source **Test Data Document:** 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 16 printed circuit **Specification Data:** 81349-mil-m-38510/176 government specification Shelf Life: N/a Unit Of Measure:

**Demilitarization:** Yes - demil/mli

## NSN 5962-01-211-6320

Digital Microcircuit - Page 2 of 2

**Fiig:** A458a0

