## NSN 5962-01-212-2654

Digital Microcircuit - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5962-01-212-2654

Rod	y Length:
	0 inches
	y Width:
	veen 0.220 inches and 0.310 inches
	y Height:
	5 inches
	imum Power Dissipation Rating:
	0 milliwatts
-	rating Tempurature Range: //+125.0 degrees celsius
	-
	age Tempurature Range:
	0/+150.0 degrees celsius
	olithic and schottky and hermetically sealed
	osure Material:
	imic or glass or plastic
	osure Configuration:
	-in-line
	but Logic Form:
	sistor-transistor logic
-	t Circuit Pattern:
12 ir	
	ign Function And Quantity:
	lector, data, multiplexer
	e Outline Source And Designator:
	mil-m-38510
	ninal Surface Treatment:
Golo	
Volt	age Rating And Type Per Characteristic:
	volts power source
	cious Material And Location:
Terr	ninal surface option gold
Pred	cious Material:
Gold	
Test	Data Document:
8134	19-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
form	at; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
envi	ronmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terr	ninal Type And Quantity:
16 p	rinted circuit
Spe	cification Data:
8134	I9-mil-m-38510/339 government specification
She	If Life:
NI/o	

## NSN 5962-01-212-2654

Digital Microcircuit - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

