## NSN 5962-01-212-2692

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-212-2692

| Body Length:   |
|--|
| Between 0.370 inches and 0.380 inches  |
| Body Width:  |
| Between 0.370 inches and 0.380 inches  |
| Body Height:   |
| Between 0.070 inches and 0.085 inches  |
| Maximum Power Dissipation Rating:  |
| 495.0 milliwatts   |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| Features Provided:   |
| Monolithic and schottky and low power and 3-state output   |
| Inclosure Material:  |
| Ceramic  |
| Inclosure Configuration:   |
| Flat pack  |
| Output Logic Form:   |
| Transistor-transistor logic  |
| Input Circuit Pattern:   |
| 16 input   |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| 7.0 volts power source   |
| Time Rating Per Chacteristic:  |
| 75.00 nanoseconds propagation delay time, low to high level output   |
| Memory Device Type:  |
| Ram  |
| Test Data Document:  |
| 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Terminal Type And Quantity:  |
| 24 flat leads  |
| Specification Data:  |
| 81349-mil-m-38510/231 government specification   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

Yes - demil/mli

Demilitarization:

## NSN 5962-01-212-2692

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0