## NSN 5962-01-212-3410

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-212-3410

Body Length: Between 0.885 inches and 0.915 inches Body Width: Between 0.285 inches and 0.305 inches Body Height: Between 0.120 inches and 0.130 inches Operating Tempurature Range: -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius Features Provided: High speed and schottky and w/enable and 3-state output Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Imput Circuit Pattern: 12 input Time Rating Per Chacteristic: 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output Shelf Life: N/a Unit Of Measure:	
Body Width: Between 0.285 inches and 0.305 inches Body Height: Between 0.120 inches and 0.130 inches Operating Tempurature Range: -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius Features Provided: High speed and schottky and w/enable and 3-state output Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 12 input Time Rating Per Chacteristic: 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output Shelf Life: N/a Unit Of Measure:	Body Length:
Between 0.285 inches and 0.305 inches  Body Height: Between 0.120 inches and 0.130 inches  Operating Tempurature Range: -55.0 to 125.0 degrees celsius  Storage Tempurature Range: -65.0 to 150.0 degrees celsius  Features Provided: High speed and schottky and w/enable and 3-state output Inclosure Material: Ceramic Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line  Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 12 input Time Rating Per Chacteristic: 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Filig:	Between 0.885 inches and 0.915 inches
Body Height: Between 0.120 inches and 0.130 inches Operating Tempurature Range: -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius Features Provided: High speed and schottky and w/enable and 3-state output Inclosure Material: Ceramic Inclosure Material: Ceramic Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 12 input Time Rating Per Chacteristic: 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Width:
Between 0.120 inches and 0.130 inches  Operating Tempurature Range: -55.0 to 125.0 degrees celsius  Storage Tempurature Range: -65.0 to 150.0 degrees celsius  Features Provided: High speed and schottky and w/enable and 3-state output Inclosure Material: Ceramic Inclosure Onfiguration: Dual-in-line  Output Logic Form: Transistor-transistor logic Imput Circuit Pattern: 12 input Time Rating Per Chacteristic: 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output Shelf Life: N/a  Unit Of Measure:	Between 0.285 inches and 0.305 inches
Operating Tempurature Range: -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius Features Provided: High speed and schottky and w/enable and 3-state output Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 112 input Time Rating Per Chacteristic: 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output Shelf Life: N/a Unit Of Measure:	Body Height:
Storage Tempurature Range: -65.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius Features Provided: High speed and schottky and w/enable and 3-state output Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 12 input Time Rating Per Chacteristic: 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Between 0.120 inches and 0.130 inches
Storage Tempurature Range:  -65.0 to 150.0 degrees celsius  Features Provided: High speed and schottky and w/enable and 3-state output Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 12 input Time Rating Per Chacteristic: 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Operating Tempurature Range:
Features Provided: High speed and schottky and w/enable and 3-state output Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 12 input Time Rating Per Chacteristic: 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	-55.0 to 125.0 degrees celsius
Features Provided: High speed and schottky and w/enable and 3-state output Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 12 input Time Rating Per Chacteristic: 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Storage Tempurature Range:
High speed and schottky and w/enable and 3-state output  Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 12 input Time Rating Per Chacteristic: 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	-65.0 to 150.0 degrees celsius
Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 12 input Time Rating Per Chacteristic: 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Features Provided:
Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 12 input Time Rating Per Chacteristic: 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	High speed and schottky and w/enable and 3-state output
Inclosure Configuration:  Dual-in-line  Output Logic Form:  Transistor-transistor logic  Input Circuit Pattern:  12 input  Time Rating Per Chacteristic:  90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Inclosure Material:
Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 12 input Time Rating Per Chacteristic: 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ceramic
Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 12 input Time Rating Per Chacteristic: 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Inclosure Configuration:
Transistor-transistor logic Input Circuit Pattern: 12 input Time Rating Per Chacteristic: 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Dual-in-line
Input Circuit Pattern: 12 input Time Rating Per Chacteristic: 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Output Logic Form:
Time Rating Per Chacteristic:  90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Transistor-transistor logic
Time Rating Per Chacteristic: 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Input Circuit Pattern:
90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	12 input
output Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Time Rating Per Chacteristic:
Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Filig:	90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level
N/a Unit Of Measure: Demilitarization: No Filig:	output
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Filg:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	<del></del>
Fiig:	Demilitarization:
	No
A458a0	Fiig:
	A458a0