

View Online at <https://aerobasegroup.com/nsn/5962-01-213-4596>

Body Length:

Between 0.930 inches and 0.975 inches

Body Width:

Between 0.245 inches and 0.300 inches

Body Height:

0.180 inches

Operating Temperature Range:

-55.0 to 125.0 degrees celsius

Storage Temperature Range:

-65.0 to 150.0 degrees celsius

End Application:

Receiving set, countermeasures an/slr-16a

Features Provided:

Hermetically sealed and negative edge triggered and w/clear and w/clock and w/preset

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

14 input

Design Function And Quantity:

4 flip-flop, j-k

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Time Rating Per Characteristic:

30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0