## NSN 5962-01-213-6091

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-213-6091

## **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and negative outputs and positive outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Hex 1 input **Design Function And Quantity:** 6 driver, line **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -16.0 volts power source and 7.0 volts power source **Time Rating Per Chacteristic:** 200.00 nanoseconds propagation delay time, low to high level output and 200.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a Unit Of Measure: **Demilitarization:**

Yes - demil/mli

Fiig:

---

A458a0