NSN 5962-01-213-8156

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-213-8156

Body Length:

2.096 inches

Body Width:

Between 0.510 inches and 0.620 inches

Body Height:

Between 0.155 inches and 0.210 inches

Maximum Power Dissipation Rating:

1.5 watts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic and hermetically sealed

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

N-type metal oxide-semiconductor logic

Input Circuit Pattern:

14 input

Design Function And Quantity:

1 microprocessor

Case Outline Source And Designator:

D-5 mil-m-38510

Current Rating Per Characteristic:

250.00 milliamperes total supply

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.3 volts power source and 7.0 volts power source

Time Rating Per Chacteristic:

300.00 nanoseconds propagation delay time, low to high level output and 300.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

40 printed circuit

Specification Data:

81349-mil-m-38510/480 government specification

Shelf Life:

NI/o

NSN 5962-01-213-8156

Digital Microcircuit - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0