## NSN 5962-01-214-6650

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-214-6650

Body Length:
Between 0.165 inches and 0.185 inches
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Maximum Power Dissipation Rating:
350.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and monolithic
Inclosure Material:
Metal
Inclosure Configuration:
Can
Input Circuit Pattern:
Dual 2 input
Design Function And Quantity:
2 amplifier, operational, general purpose
Case Outline Source And Designator:
A-2 mil-m-38510
Current Rating Per Characteristic:
4.20 milliamperes supply
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-22.0 volts power source and 22.0 volts power source
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
10 pin
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli
Fiig:
Δ458a0