## NSN 5962-01-215-4731

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-215-4731

## **Body Length:** 0.405 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 675.0 milliwatts **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and bipolar **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 amplifier, operational, general purpose **Case Outline Source And Designator:** D-4 mil-m-38510 **Terminal Surface Treatment:** Gold or solder or tin Voltage Rating And Type Per Characteristic: 44.0 volts power source **Precious Material And Location:** Terminal surfaces option gold **Precious Material:** Gold **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 8 printed circuit Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** Yes - demil/mli

## NSN 5962-01-215-4731

Linear Microcircuit - Page 2 of 2

**Fiig:** A458a0

