NSN 5962-01-215-7634

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-215-7634

Body Length:
0.785 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
750.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
An/wqn- (v) detecting-ranging set, sonar
Features Provided:
Hermetically sealed and burn in and w/resistor and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 oscillator, voltage controlled
Case Outline Source And Designator:
D-1 mil-m-38510
Terminal Surface Treatment:
Gold or tin
Voltage Rating And Type Per Characteristic:
26.0 volts power source
Precious Material And Location:
Terminal surface option gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5962-01-215-7634

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0