NSN 5962-01-216-6203

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-216-6203

| Body Length: |
|---|
| 0.390 inches |
| Body Width: |
| Between 0.235 inches and 0.260 inches |
| Body Height: |
| Between 0.045 inches and 0.085 inches |
| Maximum Power Dissipation Rating: |
| 82.5 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Low power and schottky and monolithic and w/reset |
| Inclosure Material: |
| Ceramic and glass and metal |
| Inclosure Configuration: |
| Flat pack |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 6 input |
| Design Function And Quantity: |
| 1 counter |
| Case Outline Source And Designator: |
| F-2 mil-m-38510 |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 7.0 volts power source |
| Test Data Document: |
| 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificatio |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 14 flat leads |
| Specification Data: |
| 81349-mil-m-38510/320 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - - |

Yes - demil/mli

Demilitarization:

NSN 5962-01-216-6203

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0