NSN 5962-01-216-6942

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-216-6942 **Body Outside Diameter:** Between 0.335 inches and 0.370 inches **Body Height:** Between 0.165 inches and 0.185 inches **Maximum Power Dissipation Rating:** 200.0 milliwatts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 6625-01-138-3351 voltmeter, frequency; general purpose electronic test equipment gpete, forrestal class cv, los angeles class ssn (688), sturgeon class ssn (637), nimitz class cvn **Features Provided:** Hermetically sealed and wideband and monolithic and internally compensated and w/short circuit protection **Inclosure Material:** Metal **Inclosure Configuration:** Can **Input Circuit Pattern:** Dual 2 input **Design Function And Quantity:** 2 amplifier, operational, general purpose **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:**

18.0 volts power source

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0