

View Online at <https://aerobasegroup.com/nsn/5962-01-216-7287>

Body Length:

Between 0.750 inches and 0.780 inches

Body Width:

Between 0.245 inches and 0.275 inches

Body Height:

Between 0.140 inches and 0.160 inches

Maximum Power Dissipation Rating:

235.0 milliwatts

Storage Temperature Range:

-55.0 to 165.0 degrees celsius

End Application:

Oscilloscope an/usm-488

Features Provided:

Hermetically sealed and high speed and w/clock and w/reset

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Emitter-coupled logic

Input Circuit Pattern:

Dual 4 input

Design Function And Quantity:

2 flip-flop, d-type, master slave

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-8.0 volts power source

Time Rating Per Characteristic:

2.50 nanoseconds propagation delay time, low to high level output and 2.50 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0