## NSN 5962-01-217-4207

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-217-4207 **Body Length:** 1.300 inches **Body Width:** 0.520 inches **Body Height:** 0.205 inches **Operating Tempurature Range:** -25.0 to 75.0 degrees celsius **Storage Tempurature Range:** -65.0 to 150.0 degrees celsius **Features Provided:** Programmable and monolithic and ultraviolet erasable **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 17 input **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -0.5 volts power source and 7.0 volts power source **Time Rating Per Chacteristic:** 250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 28 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig:

A458a0

Yes - demil/mli