

View Online at <https://aerobasegroup.com/nsn/5962-01-217-4208>

**Body Length:**

Between 0.750 inches and 0.780 inches

**Body Width:**

Between 0.245 inches and 0.275 inches

**Body Height:**

Between 0.140 inches and 0.160 inches

**Maximum Power Dissipation Rating:**

100.0 milliwatts

**Operating Temperature Range:**

+0.0 to 75.0 degrees celsius

**Storage Temperature Range:**

-55.0 to 165.0 degrees celsius

**End Application:**

Oscilloscope an/usm-488

**Features Provided:**

High speed and negative outputs

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Emitter-coupled logic

**Input Circuit Pattern:**

Quad 2 input

**Design Function And Quantity:**

4 gate, nor

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-8.0 volts power source and 0.0 volts power source

**Time Rating Per Characteristic:**

2.20 nanoseconds propagation delay time, low to high level output and 2.20 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0