## NSN 5962-01-217-5605

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-217-5605

Body Length:
1.255 inches
Body Width:
0.535 inches
Body Height:
0.160 inches
Operating Tempurature Range:
+0.0 to 75.0 degrees celsius
Storage Tempurature Range:
-65.0 to 150.0 degrees celsius
Features Provided:
Bipolar and programmable and schottky
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
-
14 input
14 input
14 input Terminal Surface Treatment:
14 input Terminal Surface Treatment: Solder
14 input Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
14 input <b>Terminal Surface Treatment:</b> Solder <b>Voltage Rating And Type Per Characteristic:</b> -0.5 volts power source and 7.0 volts power source
14 input Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Memory Device Type:
14 input Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Memory Device Type: Rom
14 input Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Memory Device Type: Rom Terminal Type And Quantity:
14 input Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Memory Device Type: Rom Terminal Type And Quantity: 24 printed circuit
14 input Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Memory Device Type: Rom Terminal Type And Quantity: 24 printed circuit Shelf Life:
14 input Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Memory Device Type: Rom Terminal Type And Quantity: 24 printed circuit Shelf Life: N/a
14 input Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Memory Device Type: Rom Terminal Type And Quantity: 24 printed circuit Shelf Life: N/a
14 input Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Memory Device Type: Rom Terminal Type And Quantity: 24 printed circuit Shelf Life: N/a Unit Of Measure:
14 input Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Memory Device Type: Rom Terminal Type And Quantity: 24 printed circuit Shelf Life: N/a Unit Of Measure: 
14 input Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Memory Device Type: Rom Terminal Type And Quantity: 24 printed circuit Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli