NSN 5962-01-217-8350

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-217-8350

Body Length:

1.290 inches

Body Width:

Between 0.490 inches and 0.610 inches

Body Height:

0.195 inches

Operating Tempurature Range:

-55.0 to 125.0 degrees celsius

Storage Tempurature Range:

-65.0 to 150.0 degrees celsius

Features Provided:

W/enable and hermetically sealed and programmable and monolithic

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

14 input

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Time Rating Per Chacteristic:

300.00 nanoseconds propagation delay time, low to high level output and 300.00 nanoseconds propagation delay time, high to low level output

Memory Device Type:

Rom

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0