## NSN 5962-01-218-2773

Linear Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-218-2773

Body Length:
Between 1.210 inches and 1.230 inches
Body Width:
Between 0.579 inches and 0.591 inches
Body Height:
0.245 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hybrid and thin film and burn in and hermetically sealed and electrostatic sensitive
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
14 input
Design Function And Quantity:
1 converter, digital to analog
i convenier, digital to analog
Terminal Surface Treatment:
Terminal Surface Treatment:
Terminal Surface Treatment: Solder
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 18.0 volts power source
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 18.0 volts power source Test Data Document:
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 18.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 18.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity:
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 18.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 24 printed circuit
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 18.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 24 printed circuit Shelf Life:
Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: 18.0 volts power source  Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).  Terminal Type And Quantity: 24 printed circuit  Shelf Life: N/a
Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: 18.0 volts power source  Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).  Terminal Type And Quantity: 24 printed circuit  Shelf Life: N/a
Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: 18.0 volts power source  Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).  Terminal Type And Quantity: 24 printed circuit  Shelf Life: N/a Unit Of Measure: