NSN 5962-01-218-9266

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-218-9266 **Body Length:** 0.960 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Helicopter, carrier based asw, sh-60f; nuclear power plants; helicopter, seasprite h-2; helicopter, lamps mark iii, sh-60b **Features Provided:** Hermetically sealed and burn in and electrostatic sensitive and static operation and w/decoded output **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 16 input **Criticality Code Justification:** Feat **Case Outline Source And Designator:** D-6 mil-m-38510 **Special Features:** Item must comply with requirements of defense supply center columbus production standard no. Lo5055; weapon system essential **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Reference Number Differentiating Characteristics:** Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A458a0

Yes - demil/mli