## NSN 5962-01-219-3280

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-219-3280 **Body Length:** 0.790 inches **Body Width:** 0.310 inches **Body Height:** 0.200 inches **Maximum Power Dissipation Rating:** 875.0 milliwatts **Operating Tempurature Range:** +0.0 to 70.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius **End Application:** 6625-01-135-6685 generator, signal **Features Provided:** High speed and monolithic and adjustable **Inclosure Material:** Plastic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 1 input **Design Function And Quantity:** 2 switch, analog, single pole single throw normally closed **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 36.0 volts power source **Time Rating Per Chacteristic:** 350.00 nanoseconds propagation delay time, low to high level output and 175.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

Fiig:

A458a0