NSN 5962-01-220-6323

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-220-6323

Body Length:
Between 0.750 inches and 0.780 inches
Body Width:
Between 0.245 inches and 0.275 inches
Body Height:
Between 0.140 inches and 0.160 inches
Operating Tempurature Range:
55.0 to 125.0 degrees celsius
Storage Tempurature Range:
55.0 to 150.0 degrees celsius
Features Provided:
Hermetically sealed and negative outputs and negative edge triggered and positive edge triggered and monolithic
nclosure Material:
Ceramic
nclosure Configuration:
Dual-in-line
Output Logic Form:
Emitter-coupled logic
nput Circuit Pattern:
4 input
Design Function And Quantity:
1 multivibrator, monostable
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
0.2 volts power source
Time Rating Per Chacteristic:
5.50 nanoseconds propagation delay time, low to high level output and 5.50 nanoseconds propagation delay time, high to low level output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Filg:
A458a0