NSN 5962-01-220-6326

View Online at https://aerobasegroup.com/nsn/5962-01-220-6326

Digital Microcircuit - Page 1 of 2



Body Length: Between 0.745 inches and 0.785 inches **Body Width:** Between 0.220 inches and 0.280 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 5895-00-222-4224 communication s **Features Provided:** Hermetically sealed and positive outputs and electrostatic sensitive and high speed **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 gate, or **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** Err-060 hand pull and err-060 hand **Test Data Document:**

95105-351-5669 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-01-220-6326

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0