## NSN 5962-01-221-1053

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-221-1053

Rody Length:         1.573 incluss         Body With:         1.600 incluss         1.600 incluss         Body Height:         1.600 incluss         Body Micht:         0.400 incluss         Body Micht:         0.400 incluss         Body Micht:         0.500 influences cellsius         Storage Tempurature Range:         -50.0 influences cellsius         Storage Tempurature Range:         -50.0 influences cellsius         Body Length:         Nation Outpress cellsius         Factures Provided:         Nation Configuration:         Inclosure Configuration:         Caroling Terminet Configuration:         Input         Input         Pacification And Quantity:         Input         Input         Input         Valage Rating And Type Per Characteristict:         Stolator         Input         Storage Teamering         Storage Comment:         Storage Comment:         Storage Comment:         Nation         Storage Comment:         Nation:         Storage Comment:	View Online at https://aerobasegroup.com/nsn/5962-01-221-1053
Eddy With:         1.050 incles         Eddy Light:         0.450 incles         0.450 incles         0.450 incles         0.450 incles         0.450 incles         0.50 incles         0.50 incles         0.50 incles         0.50 incles calsus         0.50 incles calsus         6.50 in 150.0 degrees calsus         7.50 in 150.	Body Length:
1.050 inclusi         Body Height:         0.450 inclusi         Body merver Dissipation Rating:         20.0 millivatis         Derating Tempurature Range:         -50.0 150.0 degrees celsius         Body end press celsius         Factures Provided:         Role couplus and hermetically sealed and monolithic         Statereettical and to couplus and thermetically sealed and m	1.573 inches
Body Height:         0.450 Inches         Maximum Power Dissipation Rating:         20.0 millivatts         Operating Tempurature Range:         -55.0 to 150.0 degrees celsius         Brazer Tempurature Range:         -65.0 to 150.0 degrees celsius         Parature Range:         -61.0 to 20.0 degrees celsius         Parature Range:         Parature Range:         -61.0 to 20.0 degrees celsius         1 regulator, voltage         Parature Treatment:         2 regulator, voltage         2 regulator, voltage         2 regulator, voltage Rating And Type Per Characteristic:         2 robustic:         2 robustic:         2 robustic:         2 robustic:         2 robustic:         2 robustic:	Body Width:
Additional	1.050 inches
Akamen Power Dissipation Rating:         200 millivatis         201 millivatis         202 millivatis         203 molto and pareso cisius         203 molto and pareso cisius         203 molto and pareso cisius         204 molto and pareso cisius         204 molto and pareso cisius         Pareson Power and pareson cisius         Pareson Power and	Body Height:
20. miliwats         Operating Tempurature Range:         -55.0 to 150.0 degrees colesius         Storage Tempurature Range:         -63.0 to 150.0 degrees colesius         Bratures Providea:         Ratures Providea:         National Antemetically sealed and monolithic         Inclosure Material:         Matal         Inclosure Configuration:         Inclosure Configuration:         1 rapid         Design Function And Quantity:         1 rapiditor, voltage         Parters:         2 rayidator, voltage         Valage Rating And Type Per Characteristic:         2 Sol volta power source         2 rayidator, voltage         2 rayidator, voltage      <	0.450 inches
Porating Tempurature Range:         350.01 50.00 degrees celsius         Storage Tempurature Range:         1-50.01 50.00 degrees celsius         Postures Provided:         Negative outputs and hermetically sealed and monolithic         Inclosure Material:         Metal         Inclosure Configuration:         Can         Input Circuit Pattern:         1 input         Providei         National And Quantity:         1 input         Valgator, voltage         Candia Surface Treatment:         Solder         Voltage Seating And Type Per Characteristic:         Soldorseasor/1/211 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacture drawing, excluses any spacification, standard or other document that may be referenced in a basic governing drawing, such as a contractor drawing, original equipment manufacture drawing, excluses any spacification, standard or other document that may be referenced in a basic governing drawing, such as a contractor drawing, as a contractor drawing, drawing (the is the basic governing drawing, such as a contractor drawing, as a co	Maximum Power Dissipation Rating:
S5.0 to 150.0 degrees celsius         S6.0 to 150.0 degrees celsius         Features Provided:         Negative outputs and hermetically sealed and monolithic         Inclosure Material:         Metal         Inclosure Configuration:         Can         Input Circuit Pattern:         1 input         President And Quantity:         1 regulator, voltage         Zorder         Valage Rating And Type Per Characteristic:         30.0 volts power source         Testinal Surface Treatment:         3030-5e8071/211 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, such as a contractor drawing original equipment manufacturer drawing, such as a contractor drawing drawing is an experiment drawing, such as a contractor drawing drawing is an experiment drawing, such as a contractor drawing drawing is an experiment drawing, such as a contractor drawing original equipment manufacturer drawing, such as a contractor drawing original equipment manufacturer drawing, such as a contractor drawing drawing is an experiment drawing, such as a contractor drawing, drawing drawing, such as a contractor drawing, drawing, drawing drawing, drawing drawing, drawing draw	20.0 milliwatts
Sorage Tempurature Range:         -bolo 150.0 degrees celsius         Features Provide:         Negative outputs and hermetically sealed and monolithic         Incoure Material:         Motal         Incoure Material:         Motal         Incoure Onfiguration:         Can         Input Circuit Pattern:         1 input         Pregulator, voltage         Templation:         1 orgulator, voltage         Voltage Rating And Type Per Characteristic:         3 Solva power source         Templation:         1 orgulator, source on the document that may be referenced in a basic governing drawing, such as a contractor drawing, orginal equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing.         1 orgulator:         2 not         1 for Measure:         2 not         1 ord Measure:         2 not         2 not         2 not         2 not         3 not         4 not         3 not	Operating Tempurature Range:
scalarse classics         Features Provide:         Negative outputs and hermetically sealed and monolithic         Inclosure Material:         Metal         Inclosure Configuration:         Can         Input Concil Pattern:         1 input         President And Quantity:         1 regulator, voltage         Terminal Surface Treatment:         Solder         Voltage Nation Sold Solder S	-55.0 to 150.0 degrees celsius
Features Proved:         Negative outputs and hermetically sealed and monolithic         Inclosure Material:         Metal         Inclosure Configuration:         Can         Input Circuit Pattern:         1 input         Design Function And Quantity:         1 regulator, voltage         Terminal Surface Treatment:         Solder         Voltage Rating And Type Per Characteristic:         3030-Se8071/211 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing.         3 pin         Sheft In:         Na         Choft Measure:         Via         In Guasure:         Na         Distribution:	Storage Tempurature Range:
Negativo to the function of the section of the sect	-65.0 to 150.0 degrees celsius
Inclosure Material:         Metal         Inclosure Configuration:         Can         Input Circuit Pattern:         1 input         Design Function And Quantity:         1 regulator, voltage         Terminal Surface Treatment:         Solder         Voltage Rating And Type Per Characteristic:         Soldy sover source         Test Data Document:         Yolds power source         Test Data Document:         Yolds power source         Participe And Quantity:         Yolds power source         Test Data Document:         Yolds power source         Participe And Quantity:         Yold Measure:         Yold         Participe And Quantity:         Na         Choff Measure:         Image:         Participe:         Na         Participe:         Participe: <tr< td=""><td>Features Provided:</td></tr<>	Features Provided:
Metal         Icosure Configuration:         Can         Input Circuit Pattern:         1 input         Design Function And Quantity:         1 regulator, voltage         Terminal Surface Treatment:         Solder         Voltage Rating And Type Per Characteristic:         305. volts power source         Totala Sourding (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing.         Yapa         Sheft Life:         N/a         Lift Of Measure:	Negative outputs and hermetically sealed and monolithic
Can         Input Circuit Pattern:         1 input         Pesign Function And Quantity:         1 regulator, voltage         Terninal Surface Treatment:         Solder         Voltage Rating And Type Per Characteristic:         35.0 volts power source         Test Data Document:         73030-5e8071/211 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing.         Spin         Sheff Life:         N/a         Unit Of Measure:         -         -         Pomiliatization:         No         Fig:	Inclosure Material:
Can         Iput Circuit Pattern:         1 iput         Design Function And Quantity:         1 regulator, voltage         Terminal Surface Treatment:         Solder         Voltage Rating And Type Per Characteristic:         35.0 volts power source         Test Data Document:         73030-5e8071/211 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing.         Sheft Life:         Na         Sheft Life:         Na         Pointid Measure:         Image:         No         Fig:	Metal
Input Circuit Pattern:         1 input         Design Function And Quantity:         1 regulator, voltage         Terminal Surface Treatment:         Solder         Voltage Rating And Type Per Characteristic:         35.0 volts power source         Test Data Document:         73030-568071/211 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing.         Terminal Type And Quantity:         3 pin         Sheff Life:         Na         Lift Of Measure:         -         Peniltarization:         Na         Figi:	Inclosure Configuration:
1 input         Design Function And Quantity:         1 regulator, voltage         Terminal Surface Treatment:         Solder         Voltage Rating And Type Per Characteristic:         35.0 volts power source         Test Data Document:         73030-588071/211 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)         Terminal Type And Quantity:         3 pin         Shelf Life:         N/a         Int Of Measure:         -         militarization:         No         Figi;	Can
Pasign Function And Quantity:         1 regulator, voltage         Terminal Surface Treatment:         Solder         Voltage Rating And Type Per Characteristic:         35.0 volts power source         Test Data Document:         73030-5e8071/211 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)         Terminal Type And Quantity:         3 pin         Shelf Life:         N/a         In of Measure:         -         -         Pemiltarization:         No         Fig:	Input Circuit Pattern:
I regulator, voltage         Terminal Surface Treatment:         Solder         Voltage Rating And Type Per Characteristic:         35.0 volts power source         Test Data Document:         73030-5e8071/211 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)         terminal Type And Quantity:         3 pin         Shelf Life:         Iv/a         Unit Of Measure:         -         Demilitarization:         No         Fig:	1 input
Terminal Surface Treatment:         Solder         Voltage Rating And Type Per Characteristic:         35.0 volts power source         Test Data Document:         73030-5e8071/211 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)         Terminal Type And Quantity:         3 pin         Shelf Life:         N/a         Unit Of Measure:         -         Pomilitarization:         No         Fig:	Design Function And Quantity:
Solder         Voltage Rating And Type Per Characteristic:         Solo volts power source         Test Data Document:         73030-5e8071/211 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)         Terminal Type And Quantity:         3 pin         Shelf Life:         N/a         Dix of Measure:            Dimitarization:         No         Fig:	1 regulator, voltage
Voltage Rating And Type Per Characteristic:35.0 volts power sourceTest Data Document:73030-5e8071/211 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)Terminal Type And Quantity:3 pinShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig:	Terminal Surface Treatment:
35.0 volts power source Test Data Document: 73030-5e8071/211 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin 3 helf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Solder
Test Data Document:         73030-5e8071/211 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)         tec.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)         Terminal Type And Quantity:         3 pin         Shelf Life:         N/a         Unit Of Measure:         -         Demilitarization:         No         Fig:	Voltage Rating And Type Per Characteristic:
73030-5e8071/211 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) <b>Terminal Type And Quantity:</b> 3 pin <b>Shelf Life:</b> N/a <b>Unit Of Measure:</b>  <b>Demilitarization:</b> No <b>Fig:</b>	35.0 volts power source
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 3 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Terminal Type And Quantity:   3 pin   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fiig:	73030-5e8071/211 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
3 pin Shelf Life: N/a Unit Of Measure:  Demilitarization: No	etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Terminal Type And Quantity:
N/a         Unit Of Measure:            Demilitarization:         No         Fiig:	3 pin
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A458a0	Filg:
	A458a0