

View Online at <https://aerobasegroup.com/nsn/5962-01-221-8003>

**Body Length:**

0.840 inches

**Body Width:**

Between 0.220 inches and 0.310 inches

**Body Height:**

0.140 inches

**Maximum Power Dissipation Rating:**

739.0 milliwatts

**Operating Temperature Range:**

-55.0 to 125.0 degrees celsius

**Storage Temperature Range:**

-65.0 to 150.0 degrees celsius

**Features Provided:**

Schottky and bipolar and monolithic and 3-state output and programmable

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

6 input

**Case Outline Source And Designator:**

D-2 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

7.0 volts power source

**Time Rating Per Characteristic:**

80.00 nanoseconds propagation delay time, low to high level output and 80.00 nanoseconds propagation delay time, high to low level output

**Memory Device Type:**

Rom

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0