## NSN 5962-01-222-3905

Digital Microcircuit - Page 1 of 2

**Demilitarization:** Yes - demil/mli



View Online at https://aerobasegroup.com/nsn/5962-01-222-3905

Body Length:
1.060 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.130 inches and 0.185 inches
Maximum Power Dissipation Rating:
165.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Low power and hermetically sealed and 3-state output and schottky and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
10 input
Design Function And Quantity:
8 buffer, noninverting
Case Outline Source And Designator:
D-8 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
20 printed circuit
Specification Data:
81349-mil-m-38510/383 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>

## NSN 5962-01-222-3905

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0