## NSN 5962-01-223-1281

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-223-1281

Body Length:
0.840 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and monolithic and programmable and 3-state output
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
10 input
Case Outline Source And Designator:
D-2 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
Err-060 hand pull and err-060 hand
Memory Device Type:
Rom
Precious Material And Location:
Terminal surface option gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a

## NSN 5962-01-223-1281

Memory Microcircuit - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0