NSN 5962-01-223-3025

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-223-3025

Body Length: 0.840 inches Body Width: Between 0.220 inches and 0.310 inches Body Height: Between 0.140 inches and 0.185 inches Maximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and burn in and programmable and 3-state output Inclosure Material: Ceramic
Body Width: Between 0.220 inches and 0.310 inches Body Height: Between 0.140 inches and 0.185 inches Maximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and burn in and programmable and 3-state output Inclosure Material:
Between 0.220 inches and 0.310 inches Body Height: Between 0.140 inches and 0.185 inches Maximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and burn in and programmable and 3-state output Inclosure Material: Ceramic
Body Height: Between 0.140 inches and 0.185 inches Maximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and burn in and programmable and 3-state output Inclosure Material: Ceramic
Between 0.140 inches and 0.185 inches Maximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and burn in and programmable and 3-state output Inclosure Material: Ceramic
Maximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and burn in and programmable and 3-state output Inclosure Material: Ceramic
500.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and burn in and programmable and 3-state output Inclosure Material: Ceramic
Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and burn in and programmable and 3-state output Inclosure Material: Ceramic
-55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and burn in and programmable and 3-state output Inclosure Material: Ceramic
Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and burn in and programmable and 3-state output Inclosure Material: Ceramic
-65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and burn in and programmable and 3-state output Inclosure Material: Ceramic
Features Provided: Hermetically sealed and burn in and programmable and 3-state output Inclosure Material: Ceramic
Hermetically sealed and burn in and programmable and 3-state output Inclosure Material: Ceramic
Inclosure Material: Ceramic
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
10 input
Case Outline Source And Designator:
D-2 mil-m-38510
Time Rating Per Chacteristic:
Err-060 hand pull and err-060 hand
Precious Material And Location:
Terminal surface option gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Filg:
A458a0