NSN 5962-01-223-8265

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-223-8265

| Overall Height: |
|---|
| Between 0.665 inches and 0.935 inches |
| Body Outside Diameter: |
| Between 0.335 inches and 0.370 inches |
| Body Height: |
| Between 0.165 inches and 0.185 inches |
| Maximum Power Dissipation Rating: |
| 500.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| Aircraft model h-3 |
| Features Provided: |
| Hybrid and high impedance and wideband and high slew rate and low voltage and burn in |
| Inclosure Material: |
| Silicon |
| Inclosure Configuration: |
| Can |
| Input Circuit Pattern: |
| 2 input |
| Design Function And Quantity: |
| 1 amplifier, operational, general purpose |
| Terminal Surface Treatment: |
| Solder or tin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |
| |
| |