## NSN 5962-01-223-9445

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/psn/5062-01-223-0445

view Online at https://aerobasegroup.com/nsn/5962-01-223-9445
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
800.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
1440-01-142-4724 armament, subsys
Features Provided:
Hermetically sealed and monolithic and electrostatic sensitive and high speed
Inclosure Material:
Metal
Inclosure Configuration:
Can
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 2 input
Design Function And Quantity:
2 driver, peripheral
Case Outline Source And Designator:
To-99 joint electron device engineering council
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
Err-060 hand pull and err-060 hand
Precious Material And Location:
Terminal surfaces option gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
8 pin

Shelf Life:

N/a

## NSN 5962-01-223-9445

Digital Microcircuit - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0