NSN 5962-01-225-1555

Digital Microcircuit - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5962-01-225-1555 |
|--|
| Body Length: |
| 2.096 inches |
| Body Width: |
| Between 0.590 inches and 0.620 inches |
| Body Height: |
| 0.210 inches |
| Maximum Power Dissipation Rating: |
| 1.6 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and burn in and monolithic and w/clock and 3-state output and w/enable |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 27 input |
| Design Function And Quantity: |
| 1 microprocessor |
| Case Outline Source And Designator: |
| D-5 mil-m-38510 |
| Current Rating Per Characteristic: |
| 50.00 milliamperes output |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| -0.5 volts power source and 7.0 volts power source |
| Time Rating Per Chacteristic: |
| 53.00 nanoseconds propagation delay time, low to high level output and 53.00 nanoseconds propagation delay time, high to low level |
| output |
| Test Data Document: |
| 14933-84057 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 40 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5962-01-225-1555

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0