## NSN 5962-01-225-7035

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-225-7035 **Body Length:** 0.930 inches **Body Width:** 0.310 inches **Body Height:** 0.120 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and bipolar and programmable and 3-state output **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 12 input **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 7.0 volts power source **Time Rating Per Chacteristic:** 60.00 nanoseconds propagation delay time, low to high level output and 60.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Memory Capacity:** Unknown **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 18 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig:

A458a0

Yes - demil/mli