NSN 5962-01-225-9123

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-225-9123

view Offilite at https://defobasegroup.com/hsh/0302-01-225-3125
Body Length:
0.840 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
400.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and positive outputs
Inclosure Material:
Ceramic or plastic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
4 channel
Design Function And Quantity:
1 multiplexer/demultiplexer, cmos
Case Outline Source And Designator:
D-2 mil-m-38510
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
32.0 volts power source
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
16 printed circuit
Specification Data:
81349-mil-m-38510/190 government specification
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5962-01-225-9123

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0