## NSN 5962-01-226-2812

Hybrid Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-226-2812 **Body Length:** 0.980 inches **Body Width:** 0.780 inches **Body Height:** 0.210 inches **Maximum Power Dissipation Rating:** 1.6 watts **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius Storage Tempurature Range: -55.0 to 150.0 degrees celsius **Features Provided:** Bipolar and monolithic and burn in and tested to mil-std-883 and hybrid and high performance and low power **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 1 channel **Design Function And Quantity:** 1 arithmetic logic unit **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 18.0 volts power source **Hybrid Technology Type:** Monolithic **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 24 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli

Fiig:

A458a0