Digital Microcircuit - Page 1 of 2

--



View Online at https://aerobasegroup.com/nsn/5962-01-226-6275

| Body Length: | |
|---|--|
| 0.785 inches | |
| Body Width: | |
| 0.310 inches | |
| Body Height: | |
| 0.185 inches | |
| Maximum Power Dissipation Rating: | |
| 200.0 milliwatts | |
| Operating Tempurature Range: | |
| -55.0/+125.0 degrees celsius | |
| Storage Tempurature Range: | |
| -65.0/+175.0 degrees celsius | |
| Features Provided: | |
| Monolithic and positive outputs | |
| Inclosure Configuration: | |
| Dual-in-line | |
| Output Logic Form: | |
| Complementary-metal oxide-semiconductor logic | |
| Input Circuit Pattern: | |
| Quad 2 input | |
| Design Function And Quantity: | |
| 4 gate, nor | |
| Case Outline Source And Designator: | |
| D-1 mil-m-38510 | |
| Terminal Surface Treatment: | |
| Gold | |
| Voltage Rating And Type Per Characteristic: | |
| 15.5 volts power source | |
| Precious Material And Location: | |
| Terminal surfaces gold | |
| Precious Material: | |
| Gold | |
| Test Data Document: | |
| 81349-mil-m-38510 specification (includes engineering typ | be bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directorie | es, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test con | |
| Terminal Type And Quantity: | |
| 14 printed circuit | |
| Specification Data: | |
| • 81349-mil-m-38510/52 government specification | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |

NSN 5962-01-226-6275

Digital Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

