NSN 5962-01-226-8585 Linear Microcircuit - Page 1 of 2



Linear Microcircuit - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5962-01-226-8585
Body Length:
0.785 inches
Body Width:
0.310 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic
Inclosure Material:
Ceramic or plastic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 amplifier, video, differential
Case Outline Source And Designator:
D-1 mil-m-38510
Terminal Surface Treatment:
Gold or solder or tin
Voltage Rating And Type Per Characteristic:
-8.0 volts power source and 8.0 volts power source
Precious Material And Location:
Terminal surface option gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

NSN 5962-01-226-8585

Linear Microcircuit - Page 2 of 2

Fiig: A458a0

