## NSN 5962-01-227-5453

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-227-5453 **Body Length:** 0.770 inches **Body Width:** 0.262 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 175.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and negative outputs and positive outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Quad 1 input **Design Function And Quantity:** 4 receiver, line **Terminal Surface Treatment:** Gold Voltage Rating And Type Per Characteristic: 10.0 volts power source **Time Rating Per Chacteristic:** 85.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surfaces option gold **Precious Material:** Gold **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a

Demilitarization: Yes - demil/mli

**Unit Of Measure:** 

## NSN 5962-01-227-5453

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0