Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-227-5786

| Body Length:<br>1.263 inches<br>Body Width                             |
|--|
| Pody Width   |
| Body Width:  |
| 0.526 inches   |
| Body Height:   |
| 0.165 inches   |
| Maximum Power Dissipation Rating:                                      |
| 790.0 milliwatts   |
| Operating Tempurature Range:   |
| +0.0/+70.0 degrees celsius   |
| Storage Tempurature Range:   |
| -60.0/+150.0 degrees celsius   |
| Features Provided:   |
| Hermetically sealed and w/resistor and monolithic and positive outputs |
| Inclosure Material:  |
| Ceramic  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Input Circuit Pattern:   |
| 16 input   |
| Design Function And Quantity:  |
| 1 converter, digital to analog   |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:                            |
| 16.5 volts power source  |
| Time Rating Per Chacteristic:  |
| Err-060 hand pull and err-060 hand                                     |
| Terminal Type And Quantity:  |
| 24 printed circuit   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A458a0   |
|  |