

View Online at <https://aerobasegroup.com/nsn/5962-01-228-0137>

**Body Length:**

0.358 inches

**Body Width:**

0.358 inches

**Body Height:**

0.080 inches

**Maximum Power Dissipation Rating:**

31.0 milliwatts

**Operating Temperature Range:**

-55.0 to 125.0 degrees celsius

**Storage Temperature Range:**

-65.0 to 150.0 degrees celsius

**Features Provided:**

Hermetically sealed and burn in and low power and schottky and w/strobe and w/enable

**Inclosure Material:**

Ceramic and metal

**Inclosure Configuration:**

Leadless flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

12 input

**Design Function And Quantity:**

2 selector, data, multiplexer, four to one line

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

7.0 volts power source

**Time Rating Per Characteristic:**

29.00 nanoseconds propagation delay time, low to high level output and 38.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

20 leadless

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0