

View Online at <https://aerobasegroup.com/nsn/5962-01-228-0138>

Body Length:

0.358 inches

Body Width:

0.358 inches

Body Height:

0.080 inches

Maximum Power Dissipation Rating:

90.0 milliwatts

Operating Temperature Range:

-55.0 to 125.0 degrees celsius

Storage Temperature Range:

-65.0 to 150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and low power and schottky and w/clock and synchronous and reversible up/down

Inclosure Material:

Ceramic and metal

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

8 input

Design Function And Quantity:

1 counter, up/down

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Time Rating Per Characteristic:

42.00 nanoseconds propagation delay time, low to high level output and 52.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0