NSN 5962-01-228-8377

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-228-8377

Body Length:	
0.840 inches	
Body Width:	
Between 0.220	inches and 0.310 inches
Body Height:	
0.185 inches	
Maximum Pov	ver Dissipation Rating:
739.0 milliwatts	
Operating Ten	npurature Range:
-55.0/+125.0 de	egrees celsius
Storage Temp	urature Range:
-65.0/+150.0 de	egrees celsius
Features Prov	ided:
Hermetically se	ealed and burn in and 3-state output and w/enable and programmable
Inclosure Mate	erial:
Ceramic	
Inclosure Con	figuration:
Dual-in-line	
Output Logic	Form:
Transistor-trans	sistor logic
Input Circuit F	Pattern:
6 input	
Case Outline	Source And Designator:
D-2 mil-m-3851	10
Terminal Surfa	ace Treatment:
Solder	
Voltage Rating	g And Type Per Characteristic:
7.0 volts powe	or source
Time Rating P	er Chacteristic:
80.00 nanosec	onds propagation delay time, low to high level output and 80.00 nanoseconds propagation delay time, high to low level
output	
Memory Devic	се Туре:
Rom	
Memory Capa	city:
Unknown	
Test Data Doc	ument:
96906-mil-std-8	383 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type	And Quantity:
16 printed circu	Jit
Shelf Life:	
N/a	

NSN 5962-01-228-8377

Memory Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

